



Figure similar

FAST LOCK-OUT RELAY 4 CHANGE OVER CONTACTS OPERATING TIME 8MS AUXILIARY VOLTAGE: 110V DC WITH RESET PUSHBUTTON RELAIS WITHOUT SOCKET

General technical data	
type of voltage	DC
continuous current	10 A
switching behavior	bistable
design of the switching function / positively driven	Yes
response time	10 ms
Product details	
product component / LED	No
Product Functions	
manual RESET	Yes
Supply voltage	
supply voltage / at DC / rated value	110 V
Inputs / Outputs	
number of NC contacts	0
number of NO contacts	0
number of CO contacts	4
switching capacity active power / at DC / maximum	4 400 W
switching capacity active power / at DC / maximum / note	at 110V DC
Mechanical Design	
width	45 mm
height	45 mm
depth	108 mm
design of the snap-on socket base	without
Degree of protection / protection class	
protection class IP / on the front	IP40
protection class IP / rear side	IP10
Environmental conditions	
ambient temperature / during operation	-40 ... +70 °C
Further information	

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)

<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA2331-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7PA2331-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA2331-0

Tender specifications

<http://www.siemens.com/specifications>

